

UNIQUE PIECES OF WOOD



TIBET SERIES



200 X 1 2 0 0 M M

Experience the calmness and elegance of nature from the comfort of your own home. Discover the strength, textures, and tones that wood has to offer. The collection of 200x1200mm tiles is everything different you were looking for.

High quality material combined with unrivaled technology has enabled us to re-interpret some of the rarest, most refined and valuable products of nature, while also enhancing their technical and qualitative properties.





no and ired

fer ons om st, of ary es.




























OLUTIONS




efore fixing, especially tonality, caliber and material is installed. The company declines minimum joint laying has a gap of 2 mm.

ANDARD EN 14411 (ISO 13006) P BIA, E 0.5%


	STANDARDS	VALUES REQUIRED	OUR VaLUES
		RECTIFIED	MATT
		<u>+</u> 0,3%, max 1 mm	In According
	ISO 10545-2	<u>+</u> 5%, max 0,5 mm	In According
		<u>+</u> 0,3%, max 1,5 mm	In According
		<u>+</u> 0,3%, max 0,8 mm	In According
		<u>+</u> 0,4%, max 1,8 mm	In According
	ISO 10545-3	≤ 0,5%	In According
	ISO 10545-4	S≥ 1300 N	S≥ 2000 N
		R≥ 35 N/mm²	In According
	ISO 10545-7	According to classification indicater by manufacture	PEI IV
	ISO 10545-8	9 x 10 ⁻⁶ max	In According
	ISO 10545-9	Resistant	Resistant
	ISO 10545-12	Resistant	Resistant
	DIN 51130	According to the space or the working area	R9
	ISO 10545-13	Class GHC Min.	Class GHA
		Class GLC Min.	Class GLA
	ISO 10545-14	Min. class 3	5




INSTALLATIO



The longest side should be staggered no mo



The V-Shade classification indicates the level of



Light



PACKA



RECTIFIED





DHAVAL BHATT (Director) +91 9702382809



BRIDH CERAMICA

Block No.2, Rameshwar Society, Sanala Road, Opp. GIDC, Morbi - 363642. (Gujarat) INDIA.



dbhat16@gmail.com | dhaval@bridhceramica.com